



4T Motorcycle Oil

76® 4T Motorcycle Oil is a high-quality engine oil designed for use in 4-stroke cycle motorcycles and all-terrain vehicles (ATVs). It also may be used as transmission oil in motorcycles and ATVs where the manufacturer specifies the use of motor oil in the transmission.

4T Motorcycle Oil is formulated to provide excellent wear protection, to minimize the formation of sludge and varnish, and to resist viscosity and thermal breakdown at high temperatures. It also protects against rust and bearing corrosion and is resistant to excessive foam buildup and air entrainment.

4T Motorcycle Oil meets the friction test requirements of the JASO MA performance classification for use in motorcycle engines with integral clutch and transmission.

Applications

- 4-stroke cycle motorcycles and ATVs

4T Motorcycle Oil meets or exceeds the requirements of:

- API Service SM, SL
- JASO MA

Features/Benefits

- Resists viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against scuffing and wear
- Protects against rust and bearing corrosion
- Good resistance to foaming and air entrainment
- Proper frictional properties to avoid clutch slippage

**Engine Oil For
4-Stroke Cycle
Motorcycles
And ATVs**

**Customer Service
Number:
1-888-766-7676**

**Technical Hot Line:
1-800-435-7761**

**E-mail Address:
*76lubricants@
conocophillips.com***



4T Motorcycle Oil

Typical Properties

SAE Grade	10W-40	20W-50
Specific Gravity @ 60°F	0.871	0.879
Density, lbs/gal @ 60°F	7.26	7.33
Color, ASTM D1500	3.0	3.5
Flash Point (COC), °C (°F)	227 (441)	230 (446)
Pour Point, °C (°F)	<-39 (<-38)	<-36 (<-33)
Viscosity, Kinematic		
cSt @ 40°C	106	172
cSt @ 100°C	15.4	18.6
Viscosity Index	150	121
Cold Cranking Viscosity, cP	6,000	5,900
@ (°C)	(-25)	(-15)
High-Temp/High-Shear Viscosity, cP @ 150°C	3.8	4.7
Sulfated Ash, ASTM D874, wt %	0.94	0.94
Total Base Number (TBN), ASTM D2896	7.8	7.8
Phosphorus, wt %	0.077	0.077
Zinc, wt %	0.085	0.085

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.