



## Airkool HP 2-Cycle Oil

76® Airkool HP 2-Cycle Oil is a premium quality, low-ash, API TC engine oil specially formulated for use in high-output commercial chain saws, motorcycles and other air-cooled 2-stroke cycle engines. It may be used in either direct oil injection or premix engines.

Airkool HP 2-Cycle Oil has a high level of detergency to help minimize piston ring sticking and exhaust port deposits to maintain good power output in 2-stroke cycle engines. It has excellent lubricity to protect against piston and cylinder scuffing, and helps reduce spark plug fouling and preignition problems. It is pre-diluted with a high-flash solvent for easy mixing with gasoline at low temperatures for premix applications.

Airkool HP 2-Cycle Oil meets JASO FD and ISO-L-EGD low-smoke requirements.

### **Applications**

- High-output commercial chain saws that operate at 17,000-20,000 rpm
- Motorcycles, scooters and all-terrain vehicles (ATVs)
- Lawn-care equipment (mowers, weed trimmers, leaf blowers)
- Other air-cooled 2-stroke cycle engines where an API TC oil is specified<sup>(1)</sup>

Airkool HP 2-Cycle Oil meets or exceeds the requirements of:

- API Service TC
- ISO-L-EGD
- JASO FD, FC, FB

<sup>(1)</sup> **Note:** Airkool HP 2-Cycle Oil is **not** recommended for use in water-cooled, 2-stroke cycle engines. Where the engine manufacturer specifies NMMA TC-W3®, TC-WII® or TC-W® quality oil, use 76 Unimix® 2-Cycle Oil.

### **Features/Benefits**

- Low-ash formulation helps minimize engine deposits and preignition
- High detergency helps minimize piston ring sticking and reduce exhaust port blocking
- Protects against piston and cylinder scuffing
- Reduces spark plug fouling
- Excellent rust and corrosion protection

**API TC Engine Oil  
For Air-Cooled,  
2-Stroke Cycle  
Engines**

**Customer Service  
Number:  
1-888-766-7676**

**Technical Hot Line:  
1-800-435-7761**

**E-mail Address:  
76lubricants@  
conocophillips.com**

**[www.76Lubricants.com](http://www.76Lubricants.com)**

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



- Meets JASO FD low-smoke requirements
- Keeps engine parts clean
- Mixes easily with gasoline at low temperatures for premix applications
- Dyed for easy visibility when mixed with gasoline
- Suitable for either direct oil injection or premix engines<sup>(2)</sup>

<sup>(2)</sup> **Note:** For premix engines, always follow the manufacturer's recommendation for choosing the proper fuel-to-oil mixing ratio.

### Airkool HP 2-Cycle Oil

#### Typical Properties

Specific Gravity @ 60°F	0.874
Density, lbs/gal @ 60°F	7.29
Color, Visual	Blue
Flash Point (COC), °C (°F)	118 (244)
Flash Point (PMCC), °C (°F)	100 (212)
Pour Point, °C (°F)	-36 (-33)
Viscosity, Kinematic	
cSt @ 40°C	56.0
cSt @ 100°C	8.7
Viscosity Index	132
Sulfated Ash, ASTM D874, wt %	0.15

#### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.