



76 Pump Oil

76 Lubricants Pump Oil is a highly refined paraffinic mineral oil developed for drip-feed lubrication of deep-well turbine water pumps.

Pump Oil is available in one viscosity grade: ISO 46. It is a highly refined, non-compounded paraffinic mineral oil. It contains no hazardous additives that can affect water quality, and has negligible odor.

Applications

- Deep-well water pumps for domestic and agricultural use
- Vacuum pumps
- Industrial applications that require a non-compounded, ISO VG 46 mineral oil

Features/Benefits

- Contains no hazardous additives
- Low odor
- Good low-temperature properties

**Lubricating Oil For
Deep-Well Water
Pumps**

**Customer Service
Number:
1-888-766-7676**

**Technical Hot Line:
1-800-435-7761**

**E-mail Address:
76lubricants@
conocophillips.com**

www.76Lubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



76 Pump Oil
Typical Properties

ISO Grade	46
Density, g/cm ³ @ 15.6°C (60°F)	0.864
Density, lbs/gal @ 15.6°C (60°F)	7.19
Color, ASTM D1500	L 0.5
Flash Point (COC), °C (°F)	232 (450)
Pour Point, °C (°F)	-13 (9)
Viscosity,	
cSt @ 40°C	41.5
cSt @ 100°C	6.4
SUS @ 100°F	214
SUS @ 210°F	47.7
Viscosity Index	104

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2007 ConocoPhillips Company. The ConocoPhillips logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.