



76 Spindle Wet

76 Lubricants Spindle Wet is a highly refined, paraffinic mineral oil developed to lubricate the rubber doffers on mechanical cotton picking machines.

Spindle Wet is available in one viscosity grade: ISO 22. It is highly refined from select paraffinic stocks to have high natural oxidation stability, low volatility and very light color to minimize staining.

Applications

- Rubber doffers on mechanical cotton picking machines

Features/Benefits

- High natural oxidation stability
- Low volatility
- Very light color to minimize staining

**Cotton Picker
Doffer Oil**

**Customer Service
Number:
1-888-766-7676**

**Technical Hot Line:
1-800-435-7761**

**E-mail Address:
76lubricants@
conocophillips.com**

www.76Lubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



76 Spindle Wet
Typical Properties

ISO Grade	22
Density, g/cm ³ @ 15.6°C (60°F)	0.853
Density, lbs/gal @ 15.6°C (60°F)	7.10
Color, ASTM D1500	L 0.5
Flash Point (COC), °C (°F)	214 (417)
Pour Point, °C (°F)	-13 (9)
Viscosity,	
cSt @ 40°C	19.7
cSt @ 100°C	4.0
SUS @ 100°F	104
SUS @ 210°F	39.7
Viscosity Index	102
Acid Number, ASTM D974, mg KOH/g	< 0.05

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2007 ConocoPhillips Company. The ConocoPhillips logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.