



## Syncon<sup>®</sup> FG Hydraulic Fluid

Syncon FG Hydraulic Fluid is a premium quality, synthetic, food-grade antiwear hydraulic fluid developed for use in the hydraulic systems of machinery found in food processing and packaging plants and in beverage bottling plants, where incidental food contact may occur. It also is recommended for use in rotary screw and rotary vane air compressors in food and beverage plants.

Syncon FG Hydraulic Fluid is formulated with synthetic polyalphaolefin (PAO) base oils and an ashless (zinc-free) additive package to provide excellent service in hydraulic system applications. It provides excellent wear protection for hydraulic pumps and motors, and protects hydraulic system components against rust and corrosion. It has outstanding oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life. It also has excellent low-temperature properties for cold start-ups. It has good water-separating properties to minimize the formation of emulsions, and is resistant to excessive foaming that can cause poor or sluggish hydraulic system response.

Syncon FG Hydraulic Fluid meets FDA requirements and former 1998 USDA H1 guidelines for incidental food contact, and is registered by NSF International as an H1 lubricant. It meets the performance requirements of all major hydraulic pump manufacturers, and is recommended for use in all types of high-pressure, high-speed hydraulic pumps.

### **Applications**

- Bottling and canning machines
- Plastic injection blow-molding machines in food processing plants
- Rotary screw and rotary vane air compressors
- Chain drives for conveyor belts
- Electric motor bearings
- Machinery operating in freezers used to store packaged food
- Other applications that require a food-grade hydraulic fluid meeting NSF H1/1998 USDA H1 guidelines

Syncon FG Hydraulic Fluid meets the requirements of:

- FDA 21 CFR 178.3570 for incidental food contact
- NSF International and former 1998 USDA H1 guidelines for incidental food contact

**Synthetic PAO-  
Based, Food-Grade  
Hydraulic Fluid**

### **Contact Information**

**U.S. Customer  
Service:  
1-800-822-6457**

**Technical Hot Line:  
1-800-766-0050**

**International  
Customer Service:  
+1-832-486-3363  
+1-832-486-3870**

**E-mail address:  
*lubricants@  
conocophillips.com***

**<http://lubricants.conocophillips.com>**

**600 N. Dairy Ashford • 2W9000 • Houston, TX 77079**



## Features/Benefits

- Excellent wear protection for hydraulic pumps and motors
- Outstanding oxidation resistance to minimize sludge and varnish formation
- Protects against rust and corrosion
- Good water-separating properties
- Good foam resistance
- Excellent low-temperature properties for cold start-ups

## Syncon® FG Hydraulic Fluid

### Typical Properties

ISO Grade	46	68	100
Specific Gravity @ 60°F	0.831	0.837	0.844
Density, lbs/gal @ 60°F	6.93	6.98	7.04
Color, ASTM D1500	0.5	0.5	0.5
Flash Point (COC), °C (°F)	257 (495)	252 (486)	254 (489)
Pour Point, °C (°F)	-57 (-71)	-48 (-54)	-45 (-49)
Viscosity,			
cSt @ 40°C	46.8	64.2	98.0
cSt @ 100°C	7.8	9.7	12.9
SUS @ 100°F	239	329	506
SUS @ 210°F	52	59	71
Viscosity Index	135	134	127
Acid Number, ASTM D974, mg KOH/g	0.67	0.67	0.67
Copper Corrosion, ASTM D130	1a	1a	1a
Demulsibility, ASTM D1401, minutes to pass	10	10	10
Foam Test, ASTM D892	Pass	Pass	Pass
Four-Ball Wear, ASTM D4172, Scar Diameter, mm	0.39	0.37	0.38
FZG Scuffing Test, ASTM D5182, Failure Load Stage	11	11	11
Oxidation Stability, RPVOT, ASTM D2272, minutes	>1,700	>1,700	>1,700
Rust Test, ASTM D665 A&B	Pass	Pass	Pass

## Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.