



Syndustrial® Turbine Oil

Syndustrial Turbine Oil is a premium quality synthetic lubricant developed to meet the severe lubrication requirements of aero-derivative stationary and marine gas turbines.

Syndustrial Turbine Oil is formulated with synthetic polyol ester (POE) base oils and select ashless additives to provide outstanding performance and protection in gas turbines. It has outstanding oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life. It has high load-carrying capacity and excellent affinity for metal surfaces to protect against wear. It has natural detergency for improved cleanliness, and protects against rust and corrosion. It also has excellent low-temperature properties for use over a wide temperature range.

Applications

- Aero-derivative gas turbines

Syndustrial Turbine Oil meets the requirements of the following industry and OEM specifications:

- Allison 501-k, 571-k
- General Electric GEK 97310, LM Series 500 to 6000
- Rolls-Royce RB211, Avon, Olympus, Spey and Tyne turbines
- Solar Turbines ES9-224, Class III (Synthesized Ester) Turbine Oil
- U.S. Military MIL-PRF-23699F, Class STD Synthetic Turbine Oil

Features/Benefits

- Outstanding oxidation resistance and thermal stability at high temperatures
- Excellent low-temperature fluidity
- High load-carrying capacity
- Protects against rust and corrosion
- Natural detergency
- High flash point for reduced fire/explosion hazard
- Extended service intervals compared with conventional mineral oil-based lubricants

Note: Syndustrial Turbine Oil can be used as top-off for existing competitive polyol ester turbine oils of the same quality. For information on compatibility with seals, paints and plastics, please call our Technical Support Hot Line.

**Synthetic Polyol
Ester Lubricant For
Land-Based
Industrial And
Marine Gas
Turbines**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**Technical Hot Line:
1-800-766-0050**

**International
Customer Service:
+1-832-486-3363
+1-832-486-3870**

**E-mail address:
lubricants@
conocophillips.com**

www.conocophillipslubricants.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Syndustrial® Turbine Oil

Typical Properties

ISO Grade	22/32
Specific Gravity @ 60°F	0.994
Density, lbs/gal @ 60°F	8.28
Color, ASTM D1500	L 4.0
Flash Point (COC), °C (°F)	266 (511)
Pour Point, °C (°F)	-60 (-76)
Viscosity,	
cSt @ 40°C	25.5
cSt @ 100°C	5.1
SUS @ 100°F	132
SUS @ 210°F	43
Viscosity Index	131
Acid Number, SAE ARP 5088, mg KOH/g	0.18
Copper Corrosion, ASTM D130	1a
Foam Test, ASTM D892,	
Sequence I, ml	5-0
Sequence II, ml	5-0
Sequence III, ml	10-0
Particle Contamination, NAS 1639, max	6
Rust Test, ASTM D665 A&B	Pass

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2009 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.

