



Wet Gas Compressor Oil

Wet Gas Compressor Oil is a high-quality lubricant developed for the lubrication of oil-flooded rotary compressors and for cylinder lubrication in reciprocating compressors in natural gas service. It is specially formulated to minimize the effects of gas dilution and oil absorption and to resist wash-off in compressors handling “wet” gas (natural gas containing liquid hydrocarbons and/or water).

Wet Gas Compressor Oil is specially formulated to provide excellent service and protection in gas compression service. It has excellent oxidation resistance and thermal stability at high temperatures to help minimize deposit formation and provide long service life. It is compounded with an oiliness additive that provides good metal-wetting ability to help resist lubricant wash-off in the presence of wet gas. It protects against rust, corrosion and wear, and is resistant to excessive foaming that can interfere with proper lubrication.

Wet Gas Compressor Oil is particularly recommended for use in applications where the gas outlet temperature is well above the condensation point of the gas.

Applications

- Oil-flooded rotary screw, rotary lobe and rotary vane compressors handling wet natural gas
- Industrial reciprocating compressors pumping wet natural gas
- Reciprocating compressors commonly found in remote gas gathering stations

Features/Benefits

- Excellent oxidation resistance and thermal stability
- Resists lubricant “wash-off”
- Formulated to minimize the effects of gas dilution and oil absorption
- Good wear protection
- Protects against rust and corrosion
- Good foam resistance

**Compounded
Compressor Oil For
“Wet” Natural Gas
Service**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**Technical Hot Line:
1-800-766-0050**

**International
Customer Service:
+1-832-486-3363
+1-832-486-3870**

**E-mail address:
lubricants@
conocophillips.com**

www.conocophillips.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



Wet Gas Compressor Oil

Typical Properties

| | |
|---|------------|
| ISO Grade | 220 |
| Specific Gravity @ 60°F | 0.891 |
| Density, lbs/gal @ 60°F | 7.42 |
| Color, ASTM D1500 | 3.0 |
| Flash Point (COC), °C (°F) | 285 (545) |
| Pour Point, °C (°F) | -15 (5) |
| Viscosity, | |
| cSt @ 40°C | 218 |
| cSt @ 100°C | 18.5 |
| SUS @ 100°F | 1,154 |
| SUS @ 210°F | 94.6 |
| Viscosity Index | 97 |
| Acid Number, ASTM D974, mg KOH/g | 0.14 |
| Copper Corrosion, ASTM D130 | 1a |
| Demulsibility, ASTM D1401, minutes to pass | 15 |
| Foam Test, ASTM D892 | Pass |
| Four-Ball Wear, ASTM D4172, Scar Diameter, mm | 0.40 |
| Oxidation Stability, ASTM D943-04a, hours | 4,000 |
| Rust Test, ASTM D665 A&B | Pass |

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2009 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.