



VersaTrans™ ATF

VersaTrans ATF is a high-quality transmission fluid specially designed for use in automatic transmissions in most passenger cars and light trucks. It has been extensively field tested for use in most North American vehicles and in a wide variety of European and Japanese vehicles.

VersaTrans ATF has carefully balanced frictional properties for smooth shifting and excellent anti-shudder performance. It has high shear stability and excellent oxidation resistance for long service life. It provides excellent wear protection, helps protect against sludge and varnish formation, and has excellent low-temperature properties for easier shifting in cold weather.

VersaTrans ATF meets the requirements of the JASO 1A performance standard developed by Japanese automakers for service fill automatic transmission fluids.

Applications

- Chrysler automatic transmissions, except the AS68RC transmission
- Ford automatic transmissions where a MERCON®V fluid or earlier-generation MERCON® fluids (obsolete) are specified
- GM automatic transmissions in 2005 and earlier vehicles, except those that require a DEXRON®-VI fluid for warranty coverage, or a CVT fluid
- Many import vehicles, including Acura, Audi, BMW, Honda, Hyundai, Infiniti, Kia, Mazda, Mercedes-Benz, Mitsubishi, Nissan, Porsche, Saab, Saturn, Toyota, Volkswagen and Volvo⁽¹⁾
- Heavy-duty automatic and powershift transmissions in trucks and buses
- Hydraulic systems on industrial and mobile equipment operating over a wide temperature range

VersaTrans ATF is fully licensed and/or approved for service fill in the following applications:

- Allison C-4
- Ford MERCON®V
- Voith DIWA transmissions

VersaTrans ATF meets or exceeds the requirements of:

- JASO M315, Class 1A

**Multi-Vehicle
Automatic
Transmission Fluid**

Contact Information

**U.S. Customer
Service:
1-800-822-6457**

**U.S. Technical
Services Hot Line:
1-800-766-0050**

**International:
+1-832-486-3363**

**E-mail address:
lubricants@
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



⁽¹⁾ **Note:** VersaTrans ATF is **not** recommended for use in continuously variable transmissions (CVTs) or in most 6-speed or 7-speed automatic transmissions. For questions about a specific application, please call our Technical Support Hot Line.

Features/Benefits

- Extensively field tested in a wide variety of domestic and import automatic transmissions
- Proper frictional properties for smooth shifting and excellent anti-shudder performance
- Excellent oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear
- Protects against rust and corrosion
- Excellent low-temperature properties for easier shifting in cold weather
- Good seal compatibility
- Good foam resistance

VersaTrans™ ATF

Typical Properties

Specific Gravity @ 60°F	0.862
Density, lbs/gal @ 60°F	7.19
Color, Visual	Red
Flash Point (COC), °C (°F)	206 (403)
Pour Point, °C (°F)	-45 (-49)
Viscosity, Brookfield	
cP @ -40°C	12,000
Viscosity, Kinematic	
cSt @ 40°C	36.0
cSt @ 100°C	7.9
Viscosity Index	200
Zinc, wt %	<0.001

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.